

Setup and First Use

A quick guide to getting your Water Bar Supreme up and running. It covers both the tank and plumbed versions.

WHERE IT GOES

- ☐ **On a flat counter**
Level, stable and not tilted more than 10°.
- ☐ **Tap water only**
Normal municipal tap water. Not borehole water.
- ☐ **Its own plug**
A 10A wall socket. No multiplugs or adaptors.
- ☐ **Right temperature**
Room and water between 5°C and 38°C.

GETTING STARTED

- 1 Add water**

Tank version: lift out the raw water tank, fill it with fresh tap water, put it back and close the lid.

Plumbed version: have it installed first (see the Plumbed Install Procedure), then open the water supply.
- 2 Turn it on**

Plug in and hold the power key for 2 seconds.
- 3 Flush it through**

Put a bucket under the outlet and hold **Wash** for 3 seconds. The flush takes about 6 minutes. For the best water on a new unit, repeat this 3 times.
- 4 Release trapped air**

If the hydrogen window on the front is only half full, press **Normal** and run water for about 10 seconds until the level rises. The first time you use **Cold**, run it until water comes out.

YOUR BUTTONS

BUTTON	WHAT YOU GET
Cold	About 15°C or colder. PREP on the display means it is still cooling; COOL means it is ready.
Normal	Room temperature water.
Milk	About 48°C. Good for baby formula.
Coffee / Tea / Hot	About 85°C / 90°C / 95°C. Touch Lock first to release the child lock.

300 ml	Touch 300 ml, then a temperature, for a measured cup.
Temp. Control	Press it, choose Milk, Tea, Coffee or Hot, then use + and – to adjust.

Water stops automatically after 1 litre. Touch any temperature key to stop early. Keep your hand clear of the outlet when taking hot water.

READING THE LIGHTS

Purify	On while the unit is making water. Flashing while filters are being flushed.
Fresh Water (tank version)	Fill the raw water tank and empty the waste water tank.
No Water	The inner purified-water tank is empty. Wait a few minutes while it makes more.
Filter 1 / 2 / 3	White: filter is fine. Orange: about 80% used, order a replacement. Red: expired, replace it now.

The unit dims and sleeps after 60 seconds without use. Touch any key to wake it. It starts making hydrogen into the tank again.

CHANGING A FILTER

1 Open the top

Switch off. Press the ▲ button on top so the cover pops open. Turn the old filter anticlockwise and lift it out.

2 Fit the new one

Push the new filter in and turn it clockwise to tighten. Use original Zenii filters only.

3 Reset the counter

Hold **Reset** for 3 seconds, tap Reset to choose the filter you replaced, then hold Reset for 3 seconds again. Run a Wash cycle before drinking.

FILTER	TYPE	REPLACE EVERY
1	PP / carbon composite	6 to 12 months
2	Reverse osmosis (RO) membrane	12 to 24 months
3	Carbon post-filter	6 to 12 months

ERROR CODES

Note the code, then switch the unit off.

E1	The tank did not fill within 90 minutes. Check the float in the tank moves freely and the filters and tank are seated properly. On the plumbed version, check the water supply is open.
E2 / E3	Temperature sensor fault. Contact us.
E4	The water coming in is too cold. Use water between 5°C and 38°C.
E6	Heating board fault. Contact us.
E7	Heater too hot. It clears on its own once it cools down.

CARE

Unplug before cleaning. Wipe the outside with a damp cloth and never put the unit in water. On the tank version, clean the tank regularly and use citric acid to remove scale. If you won't use it for a while, clean and dry it and store it somewhere dry and ventilated.